



尺寸 Dimensions (mm)

Series	A	B	C(Φ)	D	E(Φ)
B	10±0.5	35±3	3.0±0.5	≤3.5	0.54±0.05

关键特性 Key Features

- 陶瓷管
Ceramic Tube
- 一次性过温保护
One-time Over Temperature Protection
- 合金型温度保险丝
Alloy Type Thermal-link
- 环保型产品
RoHS & REACH Compliant

应用领域 Applications

- 电机 Motors
- 电池 Batteries
- 变压器 Transformers
- 灯具 Lamps and Lanterns
- 开关电源
Switched-Mode Power Supply
- 家用电器
Home Electrical Appliances

特殊定制 Customized

其它温度及引脚长度可定制。
Other temperatures can be customized such as: 85°C, 90°C, 92°C, 95°C, 97°C, 100°C, 103°C, 108°C, 117°C, 120°C, 127°C, and etc.
The length of lead wires can be customized as required.

包装信息 Packaging Information

产品包装数量 QTY:
50Kpcs/箱 Carton
外箱尺寸 Carton Size: (mm)
440×300×260

安规认证 Agency Approvals

- UL/cUL: E214712
- TUV: R50259434
- PSE: 09020123/24
- CCC: 2009010205350867
- KTL: SU05023-11001/2/3

技术参数 Specifications

型号 Model	额定 温度 T _f (°C)	熔断 温度 Fusing Temp. (°C)	保持 温度 T _h (°C)	极限 温度 T _m (°C)	额定 电流 I _r (A)	额定 电压 U _r (V)	UL [®]	cUL [®]	TUV	PSE	CCC	KTL	ROHS REACH
							UL	cUL	TUV	PSE	CCC	KTL	REACH
B0	76	73±2	53	200	3	250AC			●	●	●	●	●
						125AC	●	●					●
						50DC	●	●					●
B18	86	81±2	61	200	3	250AC			●	●	●	●	●
						125AC	●	●					●
						50DC	●	●					●
B21	97	93±2	70	200	3	125AC	●	●		●			●
						50DC	●	●					●
B1	102	98±2	79	200	3	250AC			●	●	●	●	●
						125AC	●	●					●
						50DC	●	●					●
B2	115	111±2	91	200	3	250AC	●	●	●	●	●	●	●
						50DC	●	●					●
B3	125	121±2	100	200	3	250AC	●	●	●	●	●	●	●
						50DC	●	●					●
B4	130	125±2	106	200	3	250AC	●	●	●	●	●	●	●
						50DC	●	●					●
B8	133	130±2	111	200	3	250AC	●	●	●	●	●	●	●
						50DC	●	●					●
B5	135	130±2	111	200	3	250AC	●	●	●	●	●	●	●
						50DC	●	●					●
B9	136	131±2	112	200	3	250AC	●	●	●	●	●	●	●
						50DC	●	●					●
B13	139	135±2	115	200	3	250AC	●	●	●	●	●	●	●
						50DC	●	●					●
B6	145	140±2	121	200	3	250AC	●	●	●	●	●	●	●
						50DC	●	●					●
B7	150	145±2	126	200	3	250AC	●	●	●	●	●	●	●
						50DC	●	●					●
B16	160	154±2	135	200	3	250AC			●	●	●		●
						60DC			●				●
B32	205	199±3	169	250	3	250AC			●		●		●
						125AC	●	●					●
						60DC	●	●	●				●
B31	221	218±2	188	250	3	250AC	●	●	●		●		●
						125AC	●	●					●
						60DC	●	●	●				●