



尺寸 Dimensions (mm)

A	B	C(Φ)	D	E(Φ)
11.5±0.5	35±3	3.3±0.5	≤3.8	0.8±0.05

关键特性 Key Features

- 陶瓷管  
Ceramic tube
- 一次性过温保护  
One-time over temperature protection
- 合金型温度保险丝  
Alloy type Thermal-link
- 环保型产品  
Environmental-friendly products

应用领域 Applications

- 电机 Motor
- 电池 Battery
- 变压器 Transformer
- 灯具 Lamps and lanterns
- 开关电源 Power supplies
- 家用电器 Home electrical appliances

特殊定制 Customized

其它温度及引脚长度可定制。  
Other temperatures can be customized such as:85℃,90℃,92℃,95℃,97℃,100℃,103℃,108℃,117℃,120℃,127℃,And etc.  
The length of leadwires can be customized as required.

包装信息 Packing Information

产品包装数量:30Kpcs/箱  
QTY:30Kpcs/Carton  
外箱尺寸:44cm×30cm×26cm  
Carton size: 44cm×30cm×26cm

技术参数 Specifications

型号 Model	额定温度 Tf (℃)	熔断温度 Fuse-Temp (℃)	保持温度 Th (℃)	极限温度 Tm (℃)	额定电流 Ir (A)	额定电压 Ur (V)	最大浪涌 I <sub>max</sub> 8/20μs (1Time) (KA)	UL	cUL	TUV	PSE	CCC	KTL	RoHS	
C0	76	73±2	53	200	5	250AC	4			●	●	●	●	●	
						250AC	4			●	●	●	●	●	
C18	86	81±2	61	200	5	125AC	4	●	●					●	
						50DC	4	●	●					●	
						125AC	4	●	●					●	
C21	97	93±2	70	200	5	50DC	4	●	●					●	
						50DC	4	●	●					●	
C1	102	98±2	77	200	5	250AC	6			●	●	●	●	●	
						125AC	6	●	●					●	
						50DC	6	●	●					●	
C2	115	111±2	89	200	5	250AC	6	●	●	●	●	●	●	●	
					7	50DC	6	●	●					●	
C3	125	121±2	98	200	5	250AC	6	●	●	●	●	●	●	●	
					7	50DC	6	●	●					●	
C4	130	125±2	103	200	5	250AC	6	●	●	●	●	●	●	●	
					7	50DC	6	●	●					●	
C8	133	130±2	108	200	5	250AC	6	●	●	●	●	●	●	●	
					7	50DC	6	●	●					●	
C5	135	130±2	108	200	5	250AC	6	●	●	●	●	●	●	●	
					7	50DC	6	●	●					●	
C9	136	131±2	111	200	5	250AC	6	●	●	●	●	●	●	●	
					7	50DC	6	●	●					●	
C13	139	135±2	112	200	5	250AC	6	●	●	●	●	●	●	●	
					7	50DC	6	●	●					●	
C6	145	140±2	118	200	5	250AC	6	●	●	●	●	●	●	●	
					7	50DC	6	●	●					●	
C7	150	145±2	123	200	5	250AC	6	●	●	●	●	●	●	●	
					7	50DC	6	●	●					●	
C32	205	199±3	167	250	5	125AC	7	●	●	●		●	●	●	
						60DC	7	●	●	●		●	●	●	●
C31	221	218±2	186	250	5	250AC	7	●	●					●	
						125AC	7	●	●	●		●	●	●	●
						60DC	7	●	●	●		●	●	●	●

安规认证 Agency Approvals

- UL/cUL: E214712
- PSE: 09020123/24
- TUV: R50112714
- CCC: 2009010205350866
- KTL: SU05023-11001/2/3
- RoHS & REACH Compliant