



KSD-9700

| 额定动作温度 Rated Functioning ToF (°C) | 恢复温度 Reset temp. Ten (°C) | 额定电压 Voltage Ac (V) | 额定电流 Current (A) |
|---|---------------------------------|---------------------------|------------------------|
| 60 ± 5 | 40 ± 10 | 250 | 5 |
| 70 ± 5 | 50 ± 10 | 250 | 5 |
| 80 ± 5 | 55 ± 10 | 250 | 5 |
| 85 ± 5 | 60 ± 10 | 250 | 5 |
| 90 ± 5 | 65 ± 10 | 250 | 5 |
| 95 ± 5 | 70 ± 10 | 250 | 5 |
| 100 ± 5 | 75 ± 10 | 250 | 5 |
| 105 ± 5 | 80 ± 10 | 250 | 5 |
| 110 ± 5 | 80 ± 10 | 250 | 5 |
| 115 ± 5 | 80 ± 10 | 250 | 5 |
| 120 ± 5 | 80 ± 10 | 250 | 5 |
| 125 ± 5 | 80 ± 10 | 250 | 5 |
| 130 ± 5 | 90 ± 15 | 250 | 5 |
| 135 ± 5 | 90 ± 15 | 250 | 5 |
| 140 ± 5 | 90 ± 15 | 250 | 5 |
| 145 ± 5 | 90 ± 15 | 250 | 5 |
| 150 ± 5 | 90 ± 15 | 250 | 5 |