

5HF



好利来有限公司
厦门宁利电子有限公司

5 × 20mm 玻璃保险丝管 5 × 20mm GLASS FUSE, 250V


NORMAL BLOW

MODEL NO.	RATING
5HF-100	100mA
5HF-125	125mA
5HF-150	150mA
5HF-160	160mA
5HF-200	200mA
5HF-250	250mA
5HF-300	300mA
5HF-315	315mA
5HF-350	350mA
5HF-400	400mA
5HF-450	450mA
5HF-500	500mA
5HF-600	600mA
5HF-630	630mA
5HF-700	700mA
5HF-750	750mA
5HF-800	800mA
5HF-1	1A
5HF-1.2	1.2A
5HF-1.5	1.5A
5HF-1.6	1.6A
5HF-2	2A
5HF-2.5	2.5A
5HF-3	3A
5HF-3.15	3.15A
5HF-4	4A
5HF-5	5A
5HF-6	6A
5HF-6.3	6.3A
5HF-7	7A
5HF-8	8A
5HF-10	10A
5HF-12	12A
5HF-13	13A
5HF-15	15A
5HF-16	16A
5HF-20	20A
5HF-25	25A
5HF-30	30A



PACKING:

TYPE A: 100PCS / COLOR GIFT BOX



TYPE C: 10PCS / INNER BOX
10 BOXES / GIFT BOX



5X20mm LEAD TYPE GLASS FUSE
5HF-XXX / L

LEAD TYPE



2.4 Electrical Characteristics

HF

RATING	BLOWING TIME
2.1 In	30 min max
2.75 In	10ms ~ 5S